# IBU-tec - Pre- & Post-Processing

#### **Conveying and Dosing Equipment**

- Screw conveyors
- Conveyor belts
- Disc conveyors
- Pneumatic conveyors
- Gravimetric dosing unit with screw feed
- Volumetric dosing screws
- Vibration chutes (Vibration conveyors, Gravimetric feeders)
- Dosing belt scale
- Membrane pumps
- Spraying lances
- ▶ Rotary feeders
- Displacement and peristaltic pumps

#### **Exhaus Gas Treatment**

- ▶ Thermal afterburners and exhaust gas cleaning
- DeNOx systems to denitrogenize the exhaust gas
- Filter systems to remove dust from the exhaust gas
- Gas scrubbers, venture-scrubbers (wet gas scrubbers) for the removal of particulates and absorbable gases (acidic and alkaline washes)
- Dust analysis in the treated gas, final police filter
- Use of adsorbents to remove acidic components

#### **Mixing and Granulation Units**

Туре	Number on site	Typical size	Attainable throughput	Material type	Specifications / special characteristics
EIRICH Intensive mixer R2	1	Useable vol.: 3.5 l	N/A	Stainless steel	Laboratory mixer
EIRICH Intensive mixer R09	1	Useable vol.: 150 l	up to 300 kg/h	Stainless steel	Batch mixer, suitable for tests or production
EIRICH Intensive mixer R11	1	Useable vol.: 250 l	up to 1,000 kg/h	Carbon steel	Batch mixer, suitable for tests or production, automated
Cone mixer	2	1 x à 1,500 l 1 x à 2,500 l	up to 400 kg/h	Stainless steel	Batch mixer, suitable for tests or production
Lödige ploughshare mixer	5	3 x à 600 l 1 x à 300 l 1 x à 1,600 l			Batch mixer, suitable for tests or production

### **Screening and Sorting**

Туре	Number on site	Attainable throughput	Mesh dimensions	Spezifications / special characteristics
Multi-deck screening machine	1	up to 1,000 kg/h	0.1 mm to 7 mm	7 decks
Vibration-screening machine	1	up to 500 kg/h	40 μm - 1,000 μm	2 decks / ultrasound cleaning
Vibration-screening machine	1	up to 350 kg/h	40 μm - 1,000 μm	2 decks / ball cleaning
Round-vibration sieve	1	up to 350 kg/h	40 μm - 1,000 μm	2 decks / ultrasound cleaning
Single deck screen	2	up to 100 kg/h	0.2 mm to 5 mm	1 deck / only for removal of oversized and undersized particles

# **IBU-tec – Laboratory Facilities**

#### Experimental Kilns

- A gradient kiln of our own design is used to simulate processing conditions in industrial direct kilns (dynamic laboratory kiln, max. 1,500 °C)
- Pivot kiln (Carbolite) with a modifiable atmosphere, simulating sample movement (max. 1,100 °C)
- High-temperature microscope with automatic image analysis (HTM) for the determination of melting and expansion behavior (max. 1,600 °C)
- A large number of muffle furnaces (max. 1,600 °C)

#### Mineralogical Analysis

 Phase analysis using X-ray diffraction / XRD (Bruker D2 Phaser), including Rietveld analysis

#### Chemical Analysis

- Digestion (among others: fusion, microwave, acidic)
- Optical emissions spectroscopy (ICP-0ES)
- Atomic absorption spectrometer (F-AAS)
- Complexometric titration
- Colorimetry
- Photometry
- Potentiometry
- Gravimetric analysis
- Elemental analysis

## Processing Technology

- 2 agitator bead mills (Netzsch Zeta RS & LabStar)
- Spray drying (GEA Niro Minor)
- Cryomilling
- Homogenization
- Dispersing
- Stirring
- Drying
- Centrifugation

#### Fuel Analysis

- ▶ Elemental analysis (C, H, N, S)
- Ash analysis
- Calorific value measurement
- Ash melting characteristics (HTM)

### **Physical Analysis**

- Specific surface area (Brunauer-Emmett-Teller, BET) by N<sub>2</sub>-Physisorption
- Pore size distribution and pore radius distribution
- Dynamic and static laser granulometry (particle size analysis / PSD)
- ▶ Sieving analysis
- Determination of particle size, particle shape, particle distribution and strength
- ▶ Color value measurement
- Density analysis
- Light microscopy with digital image analysis